



POWERFUL LIGHT WEIGHT!

APT-2 AIR POWERED

TRACTOR FLUX RECOVERY SYSTEM



SYSTEM SHOWN IS
APT-2 MOUNTED ON
LINCOLN LT-7
TRACTOR

SPECIFICATIONS:

- **Weight (empty):** 15 lbs (Total added wt. = 12 lbs.)
- **Dimensions:** 28" H X 10" W X 8" D
- **Power Input :** Compressed air @70-100 psi, approximately 10 cfm (1/4" I.D. air line minimum).
- **Comes Complete with** 6 ft. hose nozzle, mounting brackets for APT-2 and hose mounting brackets .
Ready for installation!

LIGHTWEIGHT, RUGGED, AND POWERFUL. THE APT-2 MOUNTS EASILY ONTO MOST AUTOMATIC SUBMERGED ARC WELDING TRACTORS. ALSO IDEAL FOR OTHER APPLICATIONS WHERE SIZE AND WEIGHT ARE IMPORTANT FACTORS.

IMPORTANT FEATURES:

- **Adds no oil or water to the flux** and produces **no damage to the recovered flux particles**, since flux is never in compressed air stream.
- **Vacuum air pump is on exhaust side** and undesirable contaminants, fines and dust are discharged into a very efficient dust bag assembly.
- **No moving parts** in air pump and **no internal filters to wear out.**
- **Very efficient air pump** produces a higher vacuum, uses less air, and is quieter than most competitive models.
- **Ultra-lightweight** aluminum construction.
- **New flux is easily added to APT-2 hopper through spout** without interrupting weld, enabling indefinite weld length.

OPTIONAL ACCESSORIES:

- **Rear hose mounting bracket (RFHM-7) for Lincoln LT-& Tractor.** Use when welding is done between wheels of tractor or when tractor is riding in 45 through. (i.e. web to flange welds)

**FOR ORDERING INFORMATION
PLEASE CONTACT:**



ENGINEERING CO., INC.

34 Fruit St.
Shrewsbury, MA 01545 (U.S.A.)
Telephone: (508) 842-2224
Fax: (508) 842-3893
Web Site: weldengineering.com
[Email: sales@weldengineering.com](mailto:sales@weldengineering.com)